FertigHolz PARQUET

TECHNICAL DATA SHEET

www.**fertigholz**.com
info@fertigholz.com

MARINA XL | *Collection Maritim XL*



INSTALLATION METHODS

Floating Installation	YES
Click System	YES
All - Over Glueing	YES
Suitable For Heated Floors	YES

GRADING CRITERIA


Knotty appearance with cracks & sapwood

PRODUCT DETAILS

Collection Maritim XL

Product Range	Plank
Construction	3 Layered Engineered
Specie	Eupean Oak
Pattern	1- Strip
Process	Structured with Loopy Face Tech
Finish	Smoked & White Oiled
Profile	Click System
Edge Profile	4v Sided Bevelled Edge

Top Layer	4 mm
Thickness	15 mm
Width	260 mm
Length	2200 mm
Pack Size	3,432 m2
Grade	Heavy Rustic
Thermal Conductivity	0,14 m²K/W
Thermal Transmittance Value	0,12 m²K/W



* Please note that this a smoked/ tumed product. This reactive process will typically generate a wide range of colour variation in the product

* This technical data sheet was written by Fertig & Holz. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without pior notice to third parties.